

Box rotator 180°/200° (FEMII/III)



K53a insteek



K53c inklap

Description

- Rotator with a rotation angle of 180° (left rotation as standard)
- Extremely open construction for optimal visibility
- Plug-in or folding third fork
- Third fork in width adjustable
- High quality tipping shaft with sleeve bearing
- Complete with hydraulic hoses and quick connectors
- Equipped with balancing valve as standard
- Excluding control valve and forklift forks

Type	Maximum load	Height of the fork carrier	Frontal extension length	Center of gravity	Height third fork*	Fork carrier width	Weight
K53a-I (plug-in)	2.500 kg	FEM II; 407 mm	160 mm	131 mm	360 mm	1.000 mm	235 kg
K53a-O (foldaway)	2.500 kg	FEM II; 407 mm	160 mm	166 mm	660 mm	1.000 mm	265 kg
K53c-I (plug-in)	3.500 kg	FEM III; 508 mm	170 mm	132 mm	460 mm	1.200 mm	310 kg
K53c-O (foldaway)	3.500 kg	FEM III; 508 mm	170 mm	146 mm	760 mm	1.200 mm	345 kg

* Calculated from the top of the fork to the bottom of the fork carrier

Options

- Rotation angle up to 200°
- Right rotated instead of left rotated
- Topfork for plug-in model
- Topfork for folding model
- Hydraulic connection on fork carrier
- Rapid coupling (FEM II)
- Rapid coupling (FEM III)
- Attachment to frontloader or reachtruck