



4055 Kompakt S

4065 Kompakt S

ENGINE

Number of cylinders	4	4
Type	Common-rail diesel engine, turbocharged	Common-rail diesel engine, turbocharged
Emission Level	Stage V	Stage V
Capacity (cm ³)	3400	3400

ENGINE PERFORMANCE

Maximum engine power with Power Management (hp (kW))	-	-
Maximum engine power (hp (kW))	-	-
@ engine speed (rpm)	-	-
Rated engine power with Power Management (hp (kW))	-	-
Rated engine power (hp (kW))	58 (43)	65 (48)
Rated engine speed (rpm)	2300	2300
Maximum torque Power Management (Nm @ rpm)	-	-
Maximum torque (Nm @ rpm)	265 @ 1,300	290 @ 1,300
Torque rise Standard and Power Management (%)	48	46
Fuel tank capacity diesel / urea (litres)	90	90



4055 Kompakt S

4065 Kompakt S

STANDARD TRANSMISSION

Transmission Type	12 x 12 Synchroshift with mechanical shuttle	12 x 12 Synchroshift with mechanical shuttle
Maximum Speed Forward (kp/h)	40	40
Powershuttle	Option	Option
Creeper	Option	Option

OPTIONAL TRANSMISSION 1

Transmission Type	-	-
Maximum Speed Forward (kp/h)	-	-
Powershuttle	-	-
Creeper	-	-

OPTIONAL TRANSMISSION 2

Transmission Type	-	-
Maximum Speed Forward (km/h)	-	-
Powershuttle	-	-
Creeper	-	-

POWER TAKE OFF

PTO Type	Servo assisted / electro-hydraulic engagement optional	Servo assisted / electro-hydraulic engagement optional
Speed Standard @ rpm	540 @ 1958	540 @ 1958
Speed Optional @ rpm	540 / 540E @ 1958 / 1592	540 / 540E @ 1958 / 1592



4055 Kompakt S

4065 Kompakt S

Ground drive	Option	Option
Shaft type	1 3/8" 21 splines (1 3/8" 6 splines)	1 3/8" 21 splines (1 3/8" 6 splines)

FRONT PTO AND HITCH

Speed Standard @ rpm	-	-
Front hitch lift capacity (kg)	-	-

DRIVE AND STEERING (DRIVELINE)

2WD	-	-
4WD	Yes	Yes
Front axle suspension	-	-
Steering angle (°)	55	55
Min.turning radius (m)	3.82	3.82
Rear axle diff-lock	Electro-hydraulic	Electro-hydraulic
Service Brake Type	Hydraulically operated multiple wet disc brake, self adjusting	Hydraulically operated multiple wet disc brake, self adjusting
ABS Anti-lock braking system	-	-

HYDRAULIC SYSTEM

System Type	Pressure flow compensated pump	Pressure flow compensated pump
Max. pump flow rate Standard / Option (litres)	48	48
System pressure (bar)		



4055 Kompakt S

4065 Kompakt S

Control type	Mechanical Hitch Control (MHR)	Mechanical Hitch Control (MHR)
Max. lift capacity (kg)	2500	2500
OECD lift capacity through range @ 610 mm (kg)	2100	2100
Max. number of rear remotes valves	3	3
Max. number of mid mount valves	2	2
Remote valve timer control	-	-
Category type	Cat II	Cat II
Slip control	-	-